

R A W
E L E M E N T S



GROUNDED AND DOWN-TO-EARTH


innovation & inspiration

| Signature[®]
floorconcepts


BEDROCK

GEMSTONE shale


Coordinates with BEDROCK shale




BEDROCK
GYPSUM
8-000-000CB




BEDROCK
SILT
7-000-000CB




BEDROCK
MUDSTONE
5-000-000CB




BEDROCK
ORE
4-000-000CB




GEMSTONE
SHALE sodalite
3-129-130CB



GEMSTONE
SHALE celestite
3-104-093CB



GEMSTONE
SHALE malachite
3-071-102CB




GEMSTONE
SHALE peridot
3-126-127CB




BEDROCK
PUMICE
6-000-000CB




BEDROCK
SHALE
3-000-000CB



BEDROCK
BASALT
2-000-000CB




BEDROCK
GABBRO
1-000-000CB




GEMSTONE
SHALE angelite
3-131-132CB



GEMSTONE
SHALE ametrine
3-133-134CB



GEMSTONE
SHALE ruby
3-137-058CB




GEMSTONE
SHALE sunstone
3-135-136CB



GEMSTONE basalt

Coordinates with BEDROCK basalt


R A W
E L E M E N T S




GEMSTONE
BASALT azurite
2-118-039CB



GEMSTONE
BASALT diopase
2-120-121CB




GEMSTONE
BASALT aventurine
2-122-123CB




GEMSTONE
BASALT olivine
2-124-125CB




GEMSTONE
BASALT amethyst
2-116-117CB



GEMSTONE
BASALT tourmaline
2-107-115CB



GEMSTONE
BASALT garnet
2-113-035CB



GEMSTONE
BASALT carmelian
2-111-112CB



All RAW ELEMENTS are stocked in Comfi Bak®.
Also available in Thermo Bak™ for 50m² minimum.

BEDROCK

construction multi-level loop
yarn/fibre solution dyed nylon
pile weight 680g/m²
pile height 4mm
gauge 1/12
tile size 500mm x 500mm
total thickness 10mm
carton size 5m²
total weight 4.4kg/m²
dimensional stability <0.15%
backing Comfi Bak®
electrostatic propensity <3.0kv
fire rating ISO 9239.1 >4.5 kw/m² critical radiant flux
recommended adhesive RLA Polymers GS300
installation method ashlar, quarter turn, brick, directional
availability in stock
Thermo Bak™ option 50m² minimum
Shapes™ option 50m² minimum
Vivid 202 custom 50m² minimum
ACCS rating commercial extra heavy duty
warranty 15 years
fire suitable all areas
stain/soil Ultra Gard
sustainability GreenTag® Green Rate Level A
EPDs and Declare labels
WELL & LBC eligible

GEMSTONE

construction multi-level loop
yarn/fibre solution dyed nylon & Antron® Legacy
pile weight 714g/m²
pile height 4mm
gauge 1/12
tile size 500mm x 500mm
total thickness 10mm
carton size 5m²
total weight 4.42kg/m²
dimensional stability <0.15%
backing Comfi Bak®
electrostatic propensity <3.0kv
fire rating ISO 9239.1 >4.5 kw/m² critical radiant flux
recommended adhesive RLA Polymers GS300
installation method ashlar, quarter turn, brick, directional
availability in stock
Thermo Bak™ option 50m² minimum
Shapes™ option 50m² minimum
Vivid 202 custom 50m² minimum
ACCS rating commercial extra heavy duty
warranty 15 years
fire suitable all areas
stain/soil Ultra Gard
sustainability GreenTag® Green Rate Level A
EPDs and Declare labels
WELL & LBC eligible



*Our manufacturing process ensures no two tiles are the same.
Please note that there may be batch variations from different dye lots.



Signature[®]
floorconcepts

au 03 9401 0888
nz 0800 150 555
signaturefloors.com.au
signaturefloors.co.nz