



DIVISION


DESIGN DUALITY




ISOLATE
800FB | 800CB




DISTANCE
700FB | 700CB




SEPARATE
600FB | 600CB




SOLE
500FB | 500CB




FRACTURE
400FB | 400CB



CLASH
300FB | 300CB



DISCORD
200FB | 200CB



OPPOSE
100FB | 100CB

FB – Flexi Bak®
CB – Comfi Bak®


SPECIFICATIONS

Collection	Design Duality
Product	Division
Product Category	Carpet Tile
Construction	Multi-level Loop
Yarn/Fibre	Solution Dyed Nylon
Pile Weight	610g/m ² (18oz)
Pile Height	4mm
Gauge	1/12
Tile Size	500 x 500mm
Total Thickness	6.5mm Flexi Bak® 9.0mm Comfi Bak®
Total Weight	3.5kg/m ² Flexi Bak® 4.2kg/m ² Comfi Bak®
Carton Size	5m ²

CUSTOM OPTIONS

Flexi Bak®	In stock
Comfi Bak®	In stock
Thermo Bak®	50m ² minimum
Shapes by Signature®	50m ² minimum

INSTALLATION METHODS



PERFORMANCE

Dimensional Stability	<0.15%
Backing	Flexi Bak® Comfi Bak®
Electrostatic Propensity	<3.0kv
Recommended Adhesive	RLA Polymers GS300
ACCS Rating	Commercial Extra Heavy Duty
Warranty	15 Year
Fire Rating ISO 9239.1	6.6kw/m ² Critical Radiant Flux (Flexi Bak®) 5.8kw/m ² Critical Radiant Flux (Comfi Bak®) Suitable all areas
Stain/Soil	Ultra Gard

SUSTAINABILITY

GreenTag® GreenRate Level A
Declare Labels
WELL & LBC Eligible

TECHNICAL DOCUMENTS

[Technical Information Guide](#)
[Care and Maintenance Guide](#)
[Warranty Guide](#)

Our manufacturing process ensures no two tiles are the same. Please note that there may be batch variations from different dye lots.