

VERVE




VERVE DRIVE 100


au 1800 150 554
nz 0800 150 555
signaturefloors.com.au
signaturefloors.co.nz

Signature


VERVE




MOXIE
800 | 800CB




BOUNCE
400 | 400CB




SPIRIT
300 | 300CB




EDGE
600 | 600CB




PASSION
200 | 200CB



FORCE
500 | 500CB



STAMINA
700 | 700CB



DRIVE
100 | 100CB

SPECIFICATIONS

Product	Verve
Product Category	Carpet Tile
Construction	Multi-level Loop
Yarn/Fibre	Solution Dyed Nylon
Pile Weight	646g/m ² (19oz)
Pile Height	4.0mm
Gauge	1/12
Tile Size	500 x 500mm
Total Thickness	7.0mm Thermo Bak® 9.5mm Comfi Bak®
Total Weight	5.0kg/m ² Thermo Bak® 4.2kg/m ² Comfi Bak®
Carton Size	5m ²

CUSTOM OPTIONS

Thermo Bak®	In stock
Comfi Bak®	In stock
Flexi Bak®	50m ² minimum
Shapes by Signature®	50m ² minimum

INSTALLATION METHODS



ASHLAR



QUARTER TURN



BRICK



DIRECTIONAL



RANDOM

PERFORMANCE

Dimensional Stability	<0.15%
Backing	Thermo Bak® Comfi Bak®
Electrostatic Propensity	<3.0kv
Recommended Adhesive	RLA Polymers GS300
ACCS Rating	Commercial Extra Heavy Duty
Warranty	15 Year
Fire Rating ISO 9239.1	5.9kw/m ² Critical Radiant Flux (Thermo Bak®) 9.3kw/m ² Critical Radiant Flux (Comfi Bak®) Suitable all areas
Stain/Soil	Ultra Gard

SUSTAINABILITY

GreenTag® GreenRate Level A
EPDs And Declare Labels
WELL & LBC Eligible

TECHNICAL DOCUMENTS

[Technical Information Guide](#)
[Care and Maintenance Guide](#)
[Warranty Guide](#)

Our manufacturing process ensures no two tiles are the same. Please note that there may be batch variations from different dye lots.